















Polycom® Conference Phone Guide

IP Conference Phones					USB-Conference
Large Room	Standard Conference Room			Small Room and Office	
SoundStation IP 7000	SoundStation Duo	CX3000	SoundStation IP 6000	SoundStation IP 5000	SS Connect
					

Connection						
Analog		•				
IP (SIP)	•	•		•	•	
Microsoft® Lync™		•	optimized		•	•
USB						•
Voice Quality						
Polycom HD Voice™ technology	•	•	•	•	•	•
Loudspeaker frequency response	160Hz – 22kHz	220Hz – 7kHz	200Hz – 7kHz	220Hz – 14kHz	250Hz – 7kHz	300Hz – 7kHz
Microphone pickup range	6m/20ft	3m/10ft	3.6m/12ft	3.6m/12ft	2m/7ft	2m/7ft
Intelligent microphone mixing	•	•	•	•	•	•
Dynamic noise reduction	•	•	•	•	•	•
Automatic gain control	•	•	•	•	•	•
Additional Features						
Resists interference from wireless devices	•	•	•	•		•
Software upgradable	•	•	•	•		•
Large display to support advanced applications	•		•			
Multi-unit connectivity	•					
Connect to external audio system	• ⁽¹⁾					•
Computer/mobile device connectivity	•				•	• ⁽²⁾
Optional Accessories						
Expansion microphones (wired)	•	•	•	•		
Wireless lapel pin microphone	•(NA only)			•(NA only)		
Video integration kit or cables	•					
Computer calling kit		•				
Mobile device cables	•	•				
Model Variants						
Power over Ethernet (PoE)	2200-40000-001		2200-15810-025	2200-15600-xxx	2200-30900-025	
AC or Power over Ethernet (PoE)	2230-40300-001	2200-19000-xxx		2200-15660-xxx	2200-30900-xxx	
USB Powered						2200-44900-xxx

¹ Optional accessory required

² Devices with powered USB

Analog Conference Phones						
Large Room	Standard Conference Room			Small Room and Office		
SoundStation VTX 1000 	SoundStation2™ 	SoundStation Duo™ 	SoundStation2W 	VoiceStation 500 	VoiceStation 300 	
Network Connectivity						
Analog	•	•	•	•	•	•
IP (SIP)			•			
Microsoft® Lync™			•			
Digital PBX		• ⁽¹⁾				
Voice Quality						
Polycom HD Voice™ technology			•			
Loudspeaker frequency response	80Hz – 7kHz ⁽³⁾	300Hz – 3300Hz	220Hz – 7kHz	300Hz – 3500Hz	300Hz – 3300Hz	300Hz – 3300Hz
Microphone pickup range	6m/20ft	3m/10ft	3m/10ft	3m/10ft	2m/7ft	2m/7ft
Intelligent microphone mixing	•	•	•	•	•	•
Dynamic noise reduction	•	•	•	•	•	•
Automatic gain control	•					
Additional Features						
Resists interference from wireless devices	•	•	•	•	•	•
Software upgradable	•		•	•		
Large display to support advanced applications						
Multi-unit connectivity						
Connect to external audio system	•	•		•		
Bluetooth connectivity						
Optional Accessories						
Expansion microphones (wired)	•	• ⁽²⁾	•	• ⁽²⁾		
Wireless lapel pin microphone	•	•				
Video integration kit or cables	•					
Computer calling kit		• ⁽²⁾	•	• ⁽²⁾	•	
Mobile device cables		• ⁽²⁾	•	• ⁽²⁾	•	
Model Variants						
	2200-07142-xxx (with EX mics only)	2200-15100-xxx (non expandable w/o display)	2200-19000-xxx	2200-07800-xxx (Expandable)	2200-17900-xxx	2200-17910-xxx
	2200-07300-xxx (w/o EX mics and subwoofer)	2200-16000-xxx (non-expandable, w/display)		2200-07880-xxx (Basic)		
	2200-07500-xxx (with subwoofers only)	2200-16200-xxx (expandable, w/display)				

¹ Models available with integration to selected digital PBX. See product details for more information.

² Available on selected models

³ SoundStation VTX to SoundStation VTX